

# Diligence WiFi Comark RF311-T

### Temperature Data Logger



**Comark Cloud** 

Comark Cloud service makes your data universally accessible from any internet enabled device. Manage your devices and make changes to any data logger settings remotely, including changing alarm levels. With the Cloud service you can:

- Store data on-line
- Monitor multiple sites
- View on mobile devices
- Have multiple users
- Receive email alerts when alarms occur or if a device needs attention

The Diligence™ WiFi RF311-T data logger measures and records the temperature of the environment in which it is situated via an internal sensor.

Comark offers two options for managing the data collected with Diligence WiFi data loggers:

- Diligence WiFi software for set up, data logging and data review on a local PC. Set up features include data logger name, choice of °F or °C scale, sample rate and high/low alarms.
- Comark Cloud has the same features as Diligence WiFi software and in addition offers unlimited storage of your temperature and humidity records. Data can be viewed for multiple locations from anywhere in the world using any internet enabled device.

The collected temperature data is transmitted via your WiFi network and when configured, the data logger can be placed anywhere within range of the WiFi network. Alarm notifications sent in real time by email and text message.

If connectivity is temporarily lost, the data logger will continue to log readings until it can communicate again with Diligence WiFi software or Comark Cloud. The range of the data logger can be extended using WiFi extenders.

The Diligence WiFi RF311-T data logger is a low powered battery device. Battery charge is typically > 6 months depending on transmission rate. The battery can be recharged via a PC or by mains power using the RF320/US power supply unit, which is available as an accessory.

#### **Features**

- Measurement range -4°F to +140°F
- Rechargeable internal lithium polymer battery
- Easy data logger set-up using free PC software application
- Built in temperature data logger with WiFi capability and integrated display
- Temperature selection in °F or °C
- Data can be viewed via the graphing tool or can be exported to MS Excel
- Configurable high and low alarms with indicator
- Alarm delay prevents false alarms due to defrost cycles or operational conditions
- Wireless connectivity to PC via WiFi
- Max and Min readings
- IEEE 802.11b/g/n compliant
- Protection rating IP55
- Memory stores all data even if WiFi is temporarily disconnected
- Fully featured LCD segment display
- Low battery indicator
- WiFi connection indicator
- USB port used for recharging (can only be recharged when the unit is between +32 to +104°F)
- Supplied with Wall Bracket and Micro USB lead

Comark Instruments 800-555-6658 sales@comarkUSA.com www.comarkUSA.com



#### **A Fluke Company**





#### **A Fluke Company**

#### **Comark Instruments**

P.O. Box 500 Beaverton, OR 97077, USA Tel: +1 (503) 643 5204 Toll Free: (800) 555 6658 Fax: +1 (503) 627 5311

Email: sales@comarkusa.com

#### **Comark Instruments**

52 Hurricane Way Norwich, Norfolk, NR6 6JB United Kingdom Tel: +44 (0) 207 942 0712 Fax: +44 (0) 207 942 0714

Fax: +44 (0) 207 942 07 14
Email: sales@comarkinstruments.com





All rights reserved. Data subject to alteration without notice. All trademarks are the property of their respective owners. Modification of this document is not permitted without written permission from Comark Instruments.


## Comark RF311-T Temperature Data Logger

#### **Specifications**

Battery Life	3-12 months depending on frequency of transmissions
USB Supply Voltage	5V (typical)
Temperature Measurement Range	-4 to +140° F
Internal Resolution	0.1°
Temperature Accuracy	
(overall error between +14°F and +122	2°F) ±0.9°F
Temperature Accuracy	
(overall error between -4°F and +140°	°F) ±1.6°F
Logging Rate (user configurable)	10 seconds to 12 hours
Transmission Period	
(user configurable)	1 minute to 12 hours
Operating Temperature Range	-4 to +140° F
Logger Dimensions	Height 3 1/4" x Width 3 3/4" x Depth 7/8"
Protection Rating	IP55
Wireless Technology	IEEE 802.11b/g/n
Temperature Selection	°C or °F
WiFi Compliance	IEEE 802.11b/g/n compliant,

supports WEP, WPA/WPA2 encryption and enterprise networks (MS-CHAPv2, PEAP, EAP-FAST, EAP-TTLS)

For more details fo the Diligence WiFi range, please see www.comarkusa.com



All Comark instruments have a minimum one year warranty unless otherwise stated. The warranty for temperature probes is six months and all other probes are unwarranted because the conditions of use are beyond our control. The Comark Warranty covers manufacturing defects and component failure and applies worldwide. In line with our policy of continuous development, we reserve the right to alter any product specification without notice. Comark has an accredited UKAS (NIST equivalent) calibration laboratory for temperature and humidity measurement and offers full service and recalibration facilities.

Comark Instruments is committed to providing quality and affordable products to the food service industry. Our thermometers and humidity testers bring speed, accuracy and reliability to the transport, testing and storing of food under HACCP guidelines. A large variety of products, well-trained staff, and a commitment to customer satisfaction mean you can come to us for answers to all your temperature measurement needs!